

SPECIFICATION SHEET

Series 650A

Wye Strainers

Size: $\frac{1}{2}$ " - 2" (15mm - 50mm)

The FEBCO Series 650A Wye Strainers are installed in water piping systems to protect expensive equipment (such as backflow preventers) from damage or failure that can be caused by foreign material in the pipeline.

Features

- Unplugged, NPT blowoff connections are situated on cover.
- Recessed screen seats assure accurate screen alignment.
- Screens are 304 stainless steel.

Pressure – Temperature

Working Pressure: Non-Shock, 200psi @ 150°F (13.8 bar @ 65°C)

Materials


Body:	Bronze ASTM B62
Cap/Cover:	Bronze ASTM B62
Gasket:	Non-asbestos
Screen:	20 Mesh

Dimensions – Weights


Size: $\frac{1}{2}$ " - 2" (15 - 50mm)

SIZE (DN)		DIMENSIONS				WEIGHT			
in.	mm	A in.	A mm	B in.	B mm	C (NPT) in.	C (NPT) mm	lbs.	kgs.
$\frac{1}{2}$	15	2 $\frac{3}{4}$	70	2 $\frac{1}{4}$	57	$\frac{1}{4}$	6	.75	.34
$\frac{3}{4}$	20	3	76	2 $\frac{9}{16}$	65	$\frac{3}{8}$	6	1.38	.62
1	25	3 $\frac{3}{4}$	95	2 $\frac{3}{4}$	70	$\frac{3}{4}$	6	2.13	.96
1 $\frac{1}{4}$	32	4 $\frac{7}{16}$	113	3 $\frac{5}{8}$	81	$\frac{3}{4}$	10	3.13	1.4
1 $\frac{1}{2}$	40	4 $\frac{15}{16}$	125	3 $\frac{7}{8}$	98	1	10	4.5	2.0
2	50	6 $\frac{1}{8}$	156	5 $\frac{1}{8}$	130	1	20	7	3.1

Note: Dimensions are nominal. Allowances must be made for normal manufacturing tolerances.



Series 650A



Job Name _____

Contractor _____

Job Location _____

Approval _____

Engineer _____


Contractor's P.O. No. _____

Approval _____

Representative _____

Capacity

650A Screwed End "Y" Type Strainer



A Division of Watts Water Technologies, Inc.

USA: 4381 N. Brawley • Ste. 102 • Fresno, CA • 93722 • Tel. (559) 441-5300 • Fax: (559) 441-5301 • www.FEBCOonline.com
 Canada: 5435 North Service Rd. • Burlington, ONT. • L7L 5H7 • Tel. (905) 332-4090 • Fax: (905) 332-7068 • www.FEBCOonline.ca

